

# Material Safety Data Sheet

(ANSI Z400.1-2004)



Printed

21.01.2013

Revision

21.01.2013 (Can) Version 4.1

Stainless Steel-Spray

## 01 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product trade name** Stainless Steel Spray  
**Product code** 111000  
**Chemical family** Stainless steel spray based on synthetic resin cement, solvent and pigments.  
**Product use** Technical aerosols  
**Manufacturer** Weicon GmbH & Co. KG  
Königsberger Straße 255,  
D-48157 Münster  
Telephone: +49 (0) 251 / 9322 - 0  
Telefax: +49 (0) 251 / 9322 - 244  
e-mail: [info@weicon.de](mailto:info@weicon.de)  
Internet : [www.weicon.de](http://www.weicon.de)

**Responsible for the safety data sheet:** [sds@gbk-ingelheim.de](mailto:sds@gbk-ingelheim.de)

**Supplier** WEICON Inc.  
20 Steckle Place, Unit 20  
Kitchener, Ontario N2E 2C3  
Telephone: 519 896 5252  
Telefax: 519 896 5254  
e-mail: [info@weicon.ca](mailto:info@weicon.ca)

**Emergency advice** 0 11 49 178 433 74 34 (CONSULTANK Lutz Harder GmbH)

## 02 HAZARDS IDENTIFICATION

**Emergency overview** DANGER: Extremely flammable. Contents under pressure.  
**Potential Health Effects** Repeated exposure may cause skin dryness or cracking.  
Inhalation of vapors may cause drowsiness and dizziness.  
**Routes of entry** Skin and eye contact and inhalation  
**Carcinogenicity** NTP:No IARC:No OSHA:No  
**WHMIS Classification**

Class A, B5, D2B



## 03 COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS#	% by wt.
Acetone	67-64-1	2.5 – 10
Propane	74-98-6	10 – 25
Butane	106-97-8	10 – 25
Ethyl acetate	141-78-6	2.5 – 10
Xylene	1330-20-7	2.5 – 10

# Material Safety Data Sheet

(ANSI Z400.1-2004)



Printed

21.01.2013

Revision

21.01.2013 (Can) Version 4.1

Stainless Steel-Spray

---

Naphtha (petroleum), hydrotreated heavy	64742-48-9	2.5 – 10
Solvent naphtha (petroleum), light arom.	64742-95-6	2.5 – 10
Dimethoxymethane;formal	109-87-5	2.5 - 10

---

## 04 FIRST AID MEASURES

<b>Skin</b>	Remove contaminated clothing immediately. In case of contact with skin wash off with soap and water. Consult a doctor if irritation persists.
<b>Eyes</b>	Wash eyes immediately with large amounts of water for about 15 minutes, especially under the eyelids. Consult an eye specialist immediately if irritation occurs.
<b>Ingestion</b>	If person is conscious, rinse mouth with water and give water to dilute stomach contents. Do not induce vomiting. Never give anything by mouth to an unconscious person. Obtain medical attention immediately.
<b>Inhalation</b>	In the event of excessive inhalation, remove the individual to fresh air and keep him immobile. In the event of symptoms seek medical assistance immediately.
<b>Physician's information</b>	The following symptoms may occur: unconsciousness, anesthetic state, headache, confusion, dizziness.

---

## 05 FIRE AND EXPLOSION DATA

<b>Flash point</b>	-97 °C
<b>Extinguishing media</b>	Dry powder, carbon dioxide, sand
<b>Extinguishing media not to be used for safety reasons</b>	water
<b>Special hazards during fire fighting</b>	Danger of bursting. Fight fires from a safe distance due to explosion hazard. Vapors are heavier than air and will spread on the ground.
<b>Hazardous combustion products</b>	Emits toxic fumes under fire conditions.
<b>Special fire-fighting procedures</b>	Use self-contained breathing apparatus and full protective clothing to prevent contact with skin and eyes. Cool endangered containers with water spray jet. Fire residues and contaminated firefighting waters must be disposed of in accordance with local regulations.

---

## 06 ACCIDENTAL RELEASE MEASURES

<b>Spill and leak procedures</b>	Ensure adequate ventilation. Wear appropriate personal protective equipment. Keep away sources of ignition. Pick up using inert absorbents and place into suitable containers for disposal.
<b>Pollution control measures</b>	Do not allow untreated product into sewers, surface or ground water.

---

# Material Safety Data Sheet

(ANSI Z400.1-2004)



Printed

21.01.2013

Revision

21.01.2013 (Can) Version 4.1

Stainless Steel-Spray

## 07 HANDLING AND STORAGE

### Handling

Use only in well ventilated area with local exhaust ventilation. Keep away from heat and ignition sources. Do not smoke. Do not spray into flames or any burning material. Do not pierce or burn even after use. Vapors can form an explosive mixture with air. Heating may cause the container to burst violently.

### Storage

Keep container tightly closed and store in cool, dry, well ventilated area away from heat. Observe precautions for storage of compressed gas cylinders and flammable material storage. Do not store with combustible materials. Protect from heat and direct solar radiation.

## 08 EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE LIMITS:

Component	CAS#	Exposure limits
Acetone	67-64-1	500 ppm TWA ACGIH
Dimethoxymethane	109-87-5	1000 ppm TWA ACGIH
Ethyl acetate	141-78-6	400 ppm TWA ACGIH
Talc respirable dust	14807-96-6	2 mg/m <sup>3</sup> TWA ACGIH
Xylene, o-, m-, p- or mixed isomers	1330-20-7	100 ppm TWA, 150 ppm STEL ACGIH

### Skin protection

Use protective clothing to prevent skin contact. Wear butyl rubber gloves; 0.7mm; 480 min.; 60 min.

### Eye protection

Use of safety glasses with side shields is recommended.

### Respiratory protection

Use NIOSH approved respirator in the event of insufficient ventilation and aerosol or mist formation.

### General Protection and Hygiene measures

Do not inhale gases/vapors/aerosols. Do not eat, drink or smoke when working. Wash hands/or face before taking breaks and at the end of work.

## 09 PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Pressurized gas	Physical form	Aerosol
Color	Silver-grey	Odor	Solvent-like
Boiling point	-44 °C		
Flashpoint	-97 °C		
Auto-ignition	235 °C		
Lower explosion limit	1.5 Vol.%		
Upper explosion limit	10.9 Vol.%		
Vapor pressure	8300 hPa at 20 °C		

**09 PHYSICAL AND CHEMICAL PROPERTIES**

Density	Not determined
Solubility in water	insoluble
Explosive properties	The product is considered non-explosive; nevertheless explosive vapor/air mixtures can be generated.

**10 STABILITY AND REACTIVITY**

Chemical stability	Stable; no decomposition if used as directed.
Hazardous decomposition products	Carbon monoxide and carbon dioxide.
Polymerization	None
Incompatibilities	Keep away from heat.

**11 TOXICOLOGICAL INFORMATION**

Acute oral LD50	>2000 mg/kg, rat
Acute dermal LD50	>2000 mg/kg, rat
Skin irritation	Low irritant effect
Eye irritation	Low irritant
Skin sensitization	Sensitization through skin contact possible.
General experience	Frequent persistent contact with the skin may cause skin irritation. Inhalation of vapors may cause narcotic effect/intoxication.

**12 ECOLOGICAL INFORMATION**

Biological degradability	Not determined
Additional information	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do not discharge product into the environment. Do not release into the aquatic environment.

**13 DISPOSAL CONSIDERATIONS**

Product disposal	Dispose in accordance with federal, state or local regulations. Empty packaging can be disposed via recyclable waste collectors.
General information	For proper waste disposal, a complete emptying of the tin is necessary.

**14 TRANSPORT INFORMATION**



Printed

21.01.2013

Revision

21.01.2013 (Can) Version 4.1

Stainless Steel-Spray

---

## 14 TRANSPORT INFORMATION

<b>TDG / DOT shipping name</b>	AEROSOLS, flammable, Class 2.1, UN 1950
<b>Marine transport IMDG</b>	AEROSOLS, flammable, Class 2.1, UN 1950
<b>Air transport ICAO/IATA</b>	AEROSOLS, flammable, Class 2.1, UN 1950

---

## 15 REGULATORY INFORMATION

**Note:** Entries under Section 15 cover only those regulations typically addressed in the MSDS generating process, such as TSCA and EPCRA/SARA Title III.

<b>USA TSCA status</b>	All of the components are on the TSCA Inventory.
<b>Canadian DSL status</b>	All of the components are listed on the DSL Inventory.
<b>SARA Title III</b>	This product contains xylene (max. 10%) which is a toxic chemical subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 372.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information by CPR.

---

## 16 OTHER INFORMATION

<b>Further information</b>	Federal and local chemical regulations should be observed.
<b>WHMIS HAZCOM Label</b>	EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE. HARMFUL BY INHALATION..

---

To the best of our knowledge, the information contained in this MSDS is accurate. It is intended to assist the user in his evaluation of the product's hazards, and safety precautions to be taken in its use. The data on this MSDS relate only to the specific material designated herein. We do not assume any liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.