MATERIAL SAFETY DATA SHEET

| SECTION I IDENTIFICATION | | | | | |
|---|--|--|--|--|--|
| SUPPLIER NAME: | PRODUCT TYPE: CARBON STEEL FILLER METALS | | | | |
| VANGUARD STEEL LTD. | FOR GAS SHIELDED ARC WELDING | | | | |
| ADDRESS: | TRADE NAME: | | | | |
| 2160 MEADOWPINE BLVD., MISSISSAUGA ONTARIO CANADA | BONARC ER70S-6 | | | | |
| TELEPHONE NUMBER: | SIZE: | | | | |
| 905-821-1100 | ALL SIZES | | | | |
| DATE PREPARED: | CLASSIFICATION | | | | |
| MARCH 6, 2009 | AWS ER70S-6 | | | | |

| SECTION II HAZARDOUS MATERIALS | | | | | |
|---------------------------------------|-------|-----------------------|------------------------------|--|--|
| COVERING AND FLUX INGREDIENTS | WT. % | TLV mg/m ³ | SUPPLEMENTAL INFORMATION | | |
| CARBON STEEL WIRE | 97.47 | 10 (*) | (*) NOT LISTED | | |
| | | | NUISANCE VALUE | | |
| CHEMICAL COMPOSITION | | | MAXIMUM 10 mg/m ³ | | |
| C 0.080 | | | | | |
| Si 0.910 | | | | | |
| Mn 1.480 | | | | | |
| P 0.010 | | | | | |
| S 0.015 | | | | | |
| TOTAL COPPER INCLUDING PLATED COATING | 0.10 | 10 (*) | | | |
| (LESS THAN) | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| OTHERS | WT. % | TLV mg/m ³ | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

SECTION III -- FIRE AND EXPLOSION HAZARD DATA

NON-FLAMMABLE:

WELDING ARC AND SPARKS CAN IGNITE COMBUSTABLES AND FLAMMABLE PRODUCTS SEE Z49.1 REFERENCED IN SECTION VI

MATERIAL SAFETY DATA SHEET

| | SECTION IV | HEALTH | HAZARD DA | TA | |
|---|--------------|------------|-----------------------|-----------------------|--------|
| THRESHOLD LIMIT VALUE: | MAXIMUM FUME | EXPOSURE | 5.0 mg/m ³ | | |
| EFFECT OF OVEREXPOSURE: | WELDING FUME | MAY RESULT | IN DISCOMFOR | SUCH AS DIZZINESS | , |
| NAUSEA OR IRRITATION OF NOSE, THROAT OR EYES | | | | | |
| ARC RAYS CAN INJURE EYES AND BURN SKIN, ELECTRIC SHOCK CAN KILL | | | | | |
| EMERGENCY AND FIRST AID PR | ROCEDURES: | CALL FC | R MEDICAL AID | . IF BREATHING IS DIF | FICULT |
| | | GIVE OX | YGEN. IN ALL C | ASES CALL A PHYSIC | IAN |

| SECTION V REACTIVITY DATA | | | | | | |
|---|----------------|---|---------------------|--|--|--|
| STABILITY | UNSTABLE | | CONDITIONS TO AVOID | | | |
| | STABLE | • | NOT NECESSARY | | | |
| INCOMPATABILITY (MATERIALS TO AVOID): NOT NECESSARY | | | | | | |
| HAZARDOUS DECOMPOSITION PRODUCTS: WELDING FUMES AND GASES CANNOT BE CLASSIFIED SIMPLY | | | | | | |
| THE COMPOSITION AND QUANTITY OF BOTH ARE DEPENDANT ON THE METAL BEING WELDING, THE PROCESS, | | | | | | |
| ELECTRODES USED AND PROCEDURE | | | | | | |
| HAZARDOUS POLYMERIZATION | MAY OCCUR | | CONDITIONS TO AVOID | | | |
| | WILL NOT OCCUR | • | NOT NECESSARY | | | |

SECTION VI -- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIALS ARE RELEASED OR SPILLED: NOT NECESSARY

WASTE DISPOSAL METHOD: USE SCRAP DISPOSAL IN AN ENVIRONMENTALLY ACCEPTALBE MANNER

ACCORDING TO LOCAL REGULATIONS UNLESS OTHERWISE NOTED.

SECTION VII -- SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: USE RESPIRABLE FUME RESPIRATOR WHEN WELDING IN CONFINED SPACE

USE ENOUGH VENTILATION: EXHAUST AT THE ARC, OR BOTH, TO KEEP FUMES AND GASES AWAY FROM YOUR

BREATHING ZONE AND THE GENERAL AREA.

PROTECTIVE GLOVES: YES, WHEN WELDING EYE PROTECTION: SHIELD NECESSARY WHEN WELDING OTHER PROTECTIVE EQUIPMENT: MAY INCLUDE ARM PROTECTORS, APRONS, SHOULDER PROTECTION, HATS, AND DARK SUBSTANTIAL CLOTHING. DO NOT ALLOW LIVE ELECTRODES TO CONTACT SKIN.

SECTION VIII -- SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HAULING AND STORING: KEEP DRY

OTHER PRECAUTIONS: READ AND UNDERSTAND THE MANUFACTURER'S INTSRUCTION AND THE

PRECAUTIONARY LABEL ON THE PRODUCT